

AKCELA ACTIFULL OT PREMIX Cod. 1794

DESCRIPTION

It is the new ready to use antifreeze/coolant developed by PETRONAS LUBRICANTS for CASE IH, STEYR agricultural machinery and CASE construction equipment. Formulated to ensure high grade protection for new generation low emissions engines, it can be perfectly used also for other engine types.

CHARACTERISTICS

Having met the strict technical standards, and passed the severe field and engine bench tests required by CASE, CASE IH and STEYR, it has obtained the official approval MAT 3624.

- | Special fully OAT (Organic Acid Technology) formulation that allows extended life and, therefore, longer coolant change intervals. Does not require the use of supplemental coolant additives (SCAs).
- | Superior protection against corrosion of the metal components of the engine and cooling system with which it comes in contact.
- | High compatibility with all non-metal components of the engine and cooling system (seals, hoses, reserve tanks, etc.).
- | Prevents cylinder liner cavitation.
- | Protects the cooling system from electrochemical corrosion generated by parasitic currents.
- | Reduces the formation of deposits in the cooling system to enhance pump efficiency and duration.
- | Improved heat transfer capability.
- | It meets the ASTM D-6210 specification for fully-formulated Ethylene-Glycol-Base engine coolant for heavy-duty engines.



ADVICE ON USE

Ready to use coolant/antifreeze. Do not add water.
Yellow coloured product.

TECHNICAL DATA

MAT 3624, ASTM D 6210 Type 3-FF,
CUMMINS CES 14603